



TOP SECRET COATINGS

P.O. Box 3007, Arlington WA. 98223
Phone: 360-651-9050 Fax: 360-548-8573
info@topsecretcoatings.com
www.topsecretctings.com

TS-646 Triple Strength Paint Stripper

TS-646

Remove Paint & Coatings Easily

Triple Strength Paint Stripper (TS-646) is a fast acting water-based paint stripper that is fast acting and effective. Just roll it on with a high nap roller cover and it liquefies paint and coatings within fifteen minutes so they can be scraped off and shoveled out. Using TS-646 Triple Strength Paint Stripper is easier than sanding, grinding or blasting.

This product contains no caustic, acid, or flammable solvent. It is highly effective; readily removing epoxy, acrylic, urethane and alkyd paints and coatings varnish and shellac safely from most surfaces. It can be used on concrete, aluminum, steel, wood and glass. Out performs typical home center and hardware store stripper / cleaners in most applications.

Recommend following with an application of TS-695 Etching Cleaner. Contains Methylene Chloride. Ventilate well when in use. Intended Use: For removing liquid concrete coatings, garage floor coatings, epoxy floor paints, varnish, lacquer, baked enamel, or shellac from concrete, metal, wood, or glass. Not intended to be used on fiberglass, PVC or plastic.

Product Features

- Easier than sanding or blasting
- Fast acting and effective
- Removes most paint and coatings
- Economical to use
- Promotes adhesion of paint and coatings

PERFORMANCE DATA SHEET

TS-646 Triple-Strength Paint Stripper

PRODUCT TYPE: Methylene Chloride Solvent Blend Paint Remover.

COLOR(S): Clear, Thixotropic Liquid.

DESCRIPTION: A fast acting paint stripper which contains no caustic, acid, or flammable solvent. This product readily removes paint, varnish, lacquer, baked enamel and shellac safely from most surfaces. It can be used on metal, wood and glass.

Intended Use: For removing paint, varnish, lacquer, baked enamel, or shellac from metal, wood, or glass.

PHYSICAL CHARACTERISTICS

VISCOSITY: Semi-Paste.

DRY TO TOUCH: N/A

WEIGHT SOLIDS: N/A

TACK FREE: N/A

VOLUME SOLIDS: N/A

WEIGHT PER GALLON: 9.90 lbs. per gal.

V.O.C.: 1175 grams per liter

COLOR RANGE: Clear

FLASH POINT: N/A

PACKAGING: 1 gallon containers

PRACTICAL COVERAGE: N/A

**** Recoat only after the stripped surface is dry and has been thoroughly cleaned.**

APPLICATION: Apply a heavy coat over surface with an inexpensive or used brush which may be discarded after use. Allow to set for 10 to 30 minutes or until the surface is broken, then scrape off with a spatula or steel wool. All surfaces to be refinished after the stripping process is completed, should be thoroughly cleaned after the paint stripper has been used. A sweeping wash with water and denatured alcohol will normally assure that the substrate is clean enough to be painted. Some painted surfaces may require more than one application of the stripper to remove stubborn areas.

THINNING: DO NOT REDUCE.

CLEAN-UP: Clean up tools and adjacent areas with warm, soapy water.